



### Figs. 1169 - 1174 Series Lights

Certified For Use on Vessels Over 20 Meters (65.6 ft.) in Length

**CONSTRUCTION:**

- Heavy Duty Cast Bronze
- Pre-Wired Medium Prefocus Socket
- 3 Feet of 16/3-SO Cable Through a Watertight Terminal Tube
  - Watertight Access Cap for Rebulbing and Cleaning
    - 120 Volt Only, Bulb Not Included
  - Rough Service Bulbs are Available

Ordering Info				Tech Info
Description	Visibility Arc	Visibility Miles	Std. Pkg. 1 Pc.	Ship Wt. Carton Lbs. Standard Pkg.
Red Side Light	112-1/2°	3	1172RE0PLB	12.4
Green Side Light	112-1/2°	3	1172GE0PLB	12.4
White Masthead Light	225°	6	1173E00PLB	12.4
White Stern Light*	135°	3	1174E00PLB	12.4
Yellow Towing Light	135°	3	1174ME0PLB	12.6
White All-Round Light*	360°	3	1169E00PLB	11.2
White All-Round Light**	360°	6	1169HE0PLB	11.2
Red All-Round Light	360°	3	1170RE0PLB	11.2
Green All-Round Light	360°	3	1170GE0PLB	11.2
Yellow All-Round Light	360°	3	1170ME0PLB	11.2

Bulb: 120 Volt  
(Not Included)  
0342004CLR or 0342RS4CLR

Mounting Bolt Size: 3/8"  
Height Overall: 9-1/4"  
Height Lens: 6-3/4"

Special lights to meet local requirements are available upon request

\*These lights are supplied with a Gray Tinted Lens

\*\*For Great Lakes use

**Fig. 1172**  
Green Side Light



**Fig. 1170**  
Green All-Round



**Fig. 1170**  
Red All-Round



**Fig. 1172**  
Red Side Light



**Fig. 1173**  
White Masthead



**Fig. 1170**  
Yellow All-Round



**Fig. 1174**  
White Stern



**IMPORTANT BULB DATA**  
To comply with UL Standard A-1104 (A.B.Y.C.), the lights listed on this page must use a PERKO Cat. No. 0342004CLR bulb or 0342RS4CLR bulb when a "Rough Service" bulb is required.

**Spare Parts Ordering Information**

Spare Lenses:

- Red: 0261001RED
- Green: 0261001GRN
- White: 0261001CLR
- Gray: 0261001GRY
- Yellow: 0261001YLW

- Lens Gasket: 1143
- O-Ring for Cap: 1119
- Medium Prefocus Socket: 0367
- Lens Retaining Clip with Bolt: 1133
- Access Cap, O-Ring and Retainer: 1105000BLK

See Page C-36 for Bulb Information.