



Fig. 1111

**IMPORTANT BULB DATA**  
To comply with Federal Requirements this light must use a PERKO Cat. No. 0342004CLR bulb or 0342RS4CLR bulb when "Rough Service" bulbs are required.

**Fig. 1111 - Special Purpose Flashing Yellow Light**

For Use on Vessels of Any Length

**CONSTRUCTION:**

- Sheet Metal, Preprimed Galvanized Steel
  - Medium Prefocus Socket
- Watertight Terminal Tube for 16/3-SO Cable
  - Sealed Flasher Unit
- Watertight Access Cap for Rebulbing and Cleaning

Designed to meet Federal Requirements for Flashing yellow 180° - 225° light for barges, canal boats, etc., that are being pushed ahead or towed along side of a tug boat. For use on 120 volt A.C. only. Federal Requirements for this light are applicable for: inland waters, the Atlantic, Pacific and Gulf coasts, intercoastal waterways and western rivers. Refer to the U.S. Inland Navigation Rules for application, configuration and technical details.

Ordering Info				
<b>Standard Pkg.</b>	<b>Visibility Miles</b>	<b>Visibility Arc</b>	<b>Flashes Per Minute</b>	<b>Ship Wt. Carton Lbs. Std. Pkg.</b>
1 Pc. 1111ME1GAL	2	225°	50-70	6.4

Tech Info
Bulb: 120 Volt (Not Included) Height Overall: 11-1/2" Height Lens: 6-3/4"

**SPARE PARTS ORDERING INFORMATION**

Flasher: 0133. Medium Prefocus Socket: 0347A00. O-Ring for Cap: 1119.  
Access Cap, O-Ring and Retainer: 1105000BLK. Lens: 0256001YLW.  
Bulb: 0342004CLR or 0342RS4CLR see Page C-36



**Fig. 1129 - Panama Canal Blue Steering Light**

For Use on Vessels of Any Length

**CONSTRUCTION:**

- Black Polymer
  - Pre-Wired Double Contact Socket with 3 Feet of 16/3-SJO Cable



Fig. 1129

Ordering Info		
<b>Std. Pkg. - 1 Pc.</b>	<b>Visibility Arc</b>	<b>Ship Wt. Carton Lbs. Standard Pkg.</b>
1129BA0BLK	135°	2.7

Tech Info
Bulb: 12, 24, 32 or 120 Volt (Not Included) Height Overall: 7-1/2" Height Lens: 4-1/4"

**SPARE PARTS ORDERING INFORMATION**

**Bulbs**  
12 Volt: 0374001CLR. Lens: 0249000BLU.  
24 Volt: 0374002CLR. O-Ring for Cap: 1119.  
32 Volt: 0374003CLR. Double Contact Socket: 0134.  
120 Volt: 0374004CLR. Polymer Access Cap, O-Ring and Retainer:  
1105000BLK.

**IMPORTANT BULB DATA**

To comply with Panama Canal Requirements this light must use a PERKO Fig. No. 0374 bulb.



Fig. 0454



Fig. 0454E  
Tapped For  
Pipe Mount

**Fig. 0454 - Pipe Mount All-Round White Whistle Light**

Certified For Use on Vessels Over 20 Meters (65.6 ft.) in Length

**CONSTRUCTION:**

- Cast Bronze
  - Medium Prefocus Socket

Ordering Info		
<b>Std. Pkg. - 1 Pc.</b>	<b>Ship Wt. Carton Lbs. Standard Pkg.</b>	<b>Visibility Miles</b>
0454E00PLB	8.6	5

Tech Info
Bulb: 120 Volt (Not Included) Height Overall: 11-1/2" Height Lens: 6-3/4" Tapped Pipe Size: 1"

**SPARE PARTS ORDERING INFORMATION**

Bulb: 0342004CLR. Lens or Cover Gasket: 1143.  
Lens: 0261001CLR. Medium Prefocus Socket: 0367.

See Page C-36 for Bulb Information.

